



> APLIKACIJE:



> TEHNIČKI PODACI:

Boja	bež
Sirovina	veštačka smola, rastvarač
Gustina (specifična težina)	1,25 g/cm ³
Temperaturna otpornost	-20°C do +80°C
Otvoreno vreme	oko 10 min.
Temperatura nanošenja	-10°C do +35°C
Ispunjavanje rupa	max. 10 mm
Inicijalni nanos	10-12 g/cm ²
Finalna čvrstoća (DIN EN 205)	5 do 6 N/mm ²
Vreme vezivanja	48 h
Pokrivanje ravnih površina	oko 300 g/m ²
Skupljanje	oko 25 %

STOP
ekserima i šrafovima!



HENKEL Srbija d.o.o. LEPKOVI

Bulevar Oslobođenja 383, 11000 Beograd, SRB

Tel: 011 207 22 50

Fax: 011 207 22 55

www.ceresit.co.rs

EXPRESS FIX

Po preporuci
Vašeg komšije!



MONTAŽNI LEPAK



MONTAŽNI LEPAK

> KARAKTERISTIKE:

- Lepi momentalno, bez potrebe za obezbeđivanjem spojeva sredstvima za mehaničko fiksiranje
- Za unutrašnje i spoljašnje radove
- Mogućnost bojenja, kada se osuši
- Vodootporan
- Za porozne i neporozne površine
- Lako nanošenje pri niskoj temperaturi od -10°C
- Bez mirisa

Novi montažni lepak **Moment Express Fix** je profesionalni lepak na bazi rastvarača, koji ima izuzetnu snagu lepljenja (60kg/cm^2), tako da smanjuje potrebu za dodatnim mehaničkim fiksiranjem (trake, ekseri, itd).

Lepi: drvo, ciglu, faser ploče, opeku, keramičke pločice, beton, lesanit ploče, gipsane ploče, lepenku, kamen, MDF, UPVC, plastiku.

Idealno rešenje za lepljenje otpalih pločica u kupatilima i kuhinjama.

60
 kg/cm^2

- › Jaka inicijalna moć
- › Direktna aplikacija
- › Snažno lepljenje (60kg/cm^2)



POBEĐUJE KONKURENCIJU VEĆ NAKON 20 sec

